



DPM 530

# MATERIAL SAFETY DATA SHEET

REC'D DEC 05 1987

97367 (4-85)

MSDS NUMBER ▶

5,270-4

PAGE 1

<b>24 HOUR EMERGENCY ASSISTANCE</b>			<b>GENERAL MSDS ASSISTANCE</b>		
SHELL: 713-473-9461 CHEMTREC: 800-424-9300			SHELL: 713-241-4819		
ACUTE HEALTH + 3	FIRE 3	REACTIVITY 0	HAZARD RATING ▶		
			LEAST - 0    SLIGHT - 1    MODERATE - 2 HIGH - 3    EXTREME - 4		
*For acute and chronic health effects refer to the discussion in Section III					



<b>SECTION I</b>		NAME
PRODUCT ▶	ISOBUTYL ALCOHOL	
CHEMICAL NAME ▶	1-PROPANOL, 2-METHYL-	
CHEMICAL FAMILY ▶	ALCOHOL	
SHELL CODE ▶	31178	

SECTION II-A		PRODUCT/INGREDIENT	
NO.	COMPOSITION	CAS NUMBER	PERCENT
P	ISOBUTYL ALCOHOL	78-83-1	100

SECTION II-B		ACUTE TOXICITY DATA	
NO.	ACUTE ORAL LD50	ACUTE DERMAL LD50	ACUTE INHALATION LC50
P	2.46 G/KG(RAT)	4.24 G/KG (RAT)	>2125 PPM/9H (MOUSE)

SECTION III HEALTH INFORMATION

THE HEALTH EFFECTS NOTED BELOW ARE CONSISTENT WITH REQUIREMENTS UNDER THE OSHA HAZARD COMMUNICATION STANDARD (29 CFR 1910.1200).

**EYE CONTACT**

LIQUID IS SEVERELY IRRITATING TO THE EYES. VAPORS MAY ALSO BE IRRITATING.

**SKIN CONTACT**

LIQUID IS MODERATELY IRRITATING TO THE SKIN. PROLONGED OR REPEATED LIQUID CONTACT CAN RESULT IN DEFATTING AND DRYING OF THE SKIN WHICH MAY RESULT IN SKIN IRRITATION AND DERMATITIS.

**INHALATION**

VAPORS MAY CAUSE IRRITATION TO THE NOSE, THROAT AND RESPIRATORY TRACT. HIGH VAPOR CONCENTRATIONS MAY CAUSE CNS DEPRESSION.

**INGESTION**

LIQUID IS MODERATELY TOXIC AND MAY BE HARMFUL IF SWALLOWED; MAY PRODUCE CNS DEPRESSION.

**SIGNS AND SYMPTOMS**

IRRITATION AS NOTED ABOVE. EARLY TO MODERATE CNS (CENTRAL NERVOUS SYSTEM) DEPRESSION MAY BE EVIDENCED BY GIDDINESS, HEADACHE, DIZZINESS AND NAUSEA; IN EXTREME CASES, UNCONSCIOUSNESS AND DEATH MAY OCCUR.

**AGGRAVATED MEDICAL CONDITIONS**

PREEXISTING EYE, SKIN AND RESPIRATORY DISORDERS MAY BE AGGRAVATED BY EXPOSURE TO THIS PRODUCT.

SEE SECTION VI FOR SUPPLEMENTAL INFORMATION.

**SECTION IV****OCCUPATIONAL EXPOSURE LIMITS**

NO.	PEL/TWA	OSHA	PEL/CEILING	TLV/TWA	ACGIH	TLV/STEL	OTHER
P	100 PPM			50 PPM		75 PPM	

**SECTION V****EMERGENCY AND FIRST AID PROCEDURES****EYE CONTACT**

IMMEDIATELY FLUSH EYES WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES WHILE HOLDING EYELIDS OPEN. GET MEDICAL ATTENTION.

**SKIN CONTACT**

FLUSH SKIN WITH WATER WHILE REMOVING CONTAMINATED CLOTHING AND SHOES. IF IRRITATION OCCURS, GET MEDICAL ATTENTION. DO NOT REUSE CLOTHING OR SHOES UNTIL CLEANED.

**INHALATION**

REMOVE VICTIM TO FRESH AIR AND PROVIDE OXYGEN IF BREATHING IS DIFFICULT. GIVE ARTIFICIAL RESPIRATION IF NOT BREATHING. GET MEDICAL ATTENTION.

**INGESTION**

DO NOT GIVE LIQUIDS IF VICTIM IS UNCONSCIOUS OR VERY DROWSY. OTHERWISE, GIVE NO MORE THAN 2 GLASSES OF WATER AND INDUCE VOMITING BY GIVING 30CC (2 TABLESPOONS) SYRUP OF IPECAC.\* IF IPECAC IS UNAVAILABLE, GIVE 2 GLASSES OF WATER AND INDUCE VOMITING BY TOUCHING FINGER TO BACK OF VICTIM'S THROAT. KEEP VICTIM'S HEAD BELOW HIPS WHILE VOMITING. GET MEDICAL ATTENTION.

**NOTE TO PHYSICIAN**

\*IF VICTIM IS A CHILD, GIVE NO MORE THAN 1 GLASS OF WATER AND 15CC (1 TABLESPOON) SYRUP OF IPECAC. IF SYMPTOMS SUCH AS LOSS OF GAG REFLEX, CONVULSIONS OR UNCONSCIOUSNESS OCCUR BEFORE EMESIS, GASTRIC LAVAGE SHOULD BE CONSIDERED FOLLOWING INTUBATION WITH A CUFFED ENDOTRACHEAL TUBE.

**SECTION VI****SUPPLEMENTAL HEALTH INFORMATION**

MICE WHICH DIED FROM A SINGLE INTRAPERITONEAL INJECTION OF ISOBUTYL ALCOHOL (IBA) SHOWED SIGNS OF LIVER DAMAGE. IBA WAS REPORTED MUTAGENIC IN A BACTERIA TEST SYSTEM.

**SECTION VII****PHYSICAL DATA**BOILING POINT: 226  
(DEG F)SPECIFIC GRAVITY: 0.80  
(H2O=1)VAPOR PRESSURE: 8.8068 DEG F  
(MM HG)MELTING POINT: -162  
(DEG F)SOLUBILITY: MODERATE  
(IN WATER)VAPOR DENSITY: 2.55  
(AIR=1)

EVAPORATION RATE (N-BUTYL ACETATE = 1): 0.62

APPEARANCE AND ODOR: COLORLESS, MOBILE LIQUID. SHARP ODOR.

-----  
SECTION VIIIFIRE AND EXPLOSION HAZARDS  
-----

FLASH POINT AND METHOD:  
86 DEG F (TCC)

FLAMMABLE LIMITS /% VOLUME IN AIR  
LOWER: 1.7 UPPER: 10.6

## EXTINGUISHING MEDIA

USE WATER FOG, "ALCOHOL" FOAM, DRY CHEMICAL OR CO2.

## SPECIAL FIRE FIGHTING PROCEDURES AND PRECAUTIONS

WARNING. FLAMMABLE. CLEAR FIRE AREA OF UNPROTECTED PERSONNEL. DO NOT ENTER CONFINED FIRE SPACE WITHOUT FULL BUNKER GEAR (HELMET WITH FACE SHIELD, BUNKER COATS, GLOVES AND RUBBER BOOTS), INCLUDING A POSITIVE PRESSURE NIOSH APPROVED SELF-CONTAINED BREATHING APPARATUS. COOL FIRE EXPOSED CONTAINERS WITH WATER.

## UNUSUAL FIRE AND EXPLOSION HAZARDS

CONTAINERS EXPOSED TO INTENSE HEAT FROM FIRES SHOULD BE COOLED WITH WATER TO PREVENT VAPOR PRESSURE BUILDUP WHICH COULD RESULT IN CONTAINER RUPTURE. CONTAINER AREAS EXPOSED TO DIRECT FLAME CONTACT SHOULD BE COOLED WITH LARGE QUANTITIES OF WATER AS NEEDED TO PREVENT WEAKENING OF CONTAINER STRUCTURE.

-----  
SECTION IXREACTIVITY  
-----

STABILITY: STABLE

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

## CONDITIONS AND MATERIALS TO AVOID:

AVOID HEAT, SPARKS, FLAME AND CONTACT WITH STRONG OXIDIZING AGENTS. DO NOT STORE OR HANDLE IN ALUMINUM EQUIPMENT AT TEMPERATURES OVER 120 DEG. F.

## HAZARDOUS DECOMPOSITION PRODUCTS

CARBON MONOXIDE AND UNIDENTIFIED ORGANIC COMPOUNDS MAY BE FORMED DURING COMBUSTION.

-----  
SECTION XEMPLOYEE PROTECTION  
-----

## RESPIRATORY PROTECTION

AVOID PROLONGED OR REPEATED BREATHING OF VAPORS. IF EXPOSURE MAY OR DOES EXCEED OCCUPATIONAL EXPOSURE LIMITS (SEC. IV) USE A NIOSH-APPROVED RESPIRATOR TO PREVENT OVEREXPOSURE. IN ACCORD WITH 29 CFR 1910.134 USE EITHER A FULL-FACE, ATMOSPHERE-SUPPLYING RESPIRATOR OR AIR-PURIFYING RESPIRATOR FOR ORGANIC VAPORS.

## PROTECTIVE CLOTHING

AVOID CONTACT WITH EYES. WEAR CHEMICAL GOGGLES IF THERE IS LIKELIHOOD OF CONTACT WITH EYES. AVOID PROLONGED OR REPEATED CONTACT WITH SKIN. WEAR CHEMICAL-RESISTANT GLOVES AND OTHER CLOTHING AS REQUIRED TO MINIMIZE CONTACT. TEST DATA FROM PUBLISHED LITERATURE AND/OR GLOVE AND CLOTHING \*

## ADDITIONAL PROTECTIVE MEASURES

\*MANUFACTURERS INDICATE THE BEST PROTECTION IS PROVIDED BY NEOPRENE, NITRILE, AND PVC. USE EXPLOSION-PROOF VENTILATION AS REQUIRED TO CONTROL VAPOR CONCENTRATIONS. AIR-DRY CONTAMINATED CLOTHING IN A WELL VENTILATED AREA, THEN LAUNDER BEFORE REUSING.

-----  
SECTION XIENVIRONMENTAL PROTECTION  
-----

## SPILL OR LEAK PROCEDURES

WARNING. FLAMMABLE. ELIMINATE ALL IGNITION SOURCES. HANDLING EQUIPMENT MUST BE GROUNDED TO PREVENT SPARKING. \*\*\* LARGE SPILLS \*\*\* EVACUATE THE HAZARD AREA OF UNPROTECTED PERSONNEL. WEAR APPROPRIATE RESPIRATOR AND PROTECTIVE CLOTHING. SHUT OFF SOURCE OF LEAK ONLY IF SAFE TO DO SO. DIKE AND CONTAIN. IF VAPOR CLOUD FORMS, WATER FOG MAY BE USED TO SUPPRESS; CONTAIN RUN-OFF. REMOVE WITH VACUUM TRUCKS OR PUMP TO STORAGE/SALVAGE VESSELS. SOAK UP RESIDUE WITH AN ABSORBENT SUCH AS CLAY, SAND OR OTHER SUITABLE MATERIAL; PLACE IN NON-LEAKING CONTAINERS FOR PROPER DISPOSAL. FLUSH AREA WITH WATER TO REMOVE TRACE RESIDUE; DISPOSE OF FLUSH SOLUTIONS AS ABOVE. \*\*\* SMALL SPILLS \*\*\* TAKE UP WITH AN ABSORBENT MATERIAL AND PLACE IN NON-LEAKING CONTAINERS; SEAL TIGHTLY FOR

PROPER DISPOSAL.

WASTE DISPOSAL

UNDER EPA-RCRA (40 CFR 261.33), IF ISOBUTYL ALCOHOL BECOMES A WASTE MATERIAL, IT WOULD BE A HAZARDOUS WASTE, HAZARDOUS WASTE NUMBER U140. REFER TO LATEST EPA OR STATE REGULATIONS REGARDING PROPER DISPOSAL.

ENVIRONMENTAL HAZARDS

EPA - COMPREHENSIVE ENVIRONMENTAL RESPONSE, COMPENSATION AND LIABILITY ACT. UNDER EPA-CERCLA ("SUPERFUND") RELEASES TO AIR, LAND OR WATER WHICH EXCEED THE REPORTABLE QUANTITY MUST BE REPORTED TO THE NATIONAL RESPONSE CENTER, 800-424-8802.

SECTION XII

SPECIAL PRECAUTIONS

KEEP LIQUID AND VAPOR AWAY FROM HEAT, SPARKS AND FLAME. SURFACES THAT ARE SUFFICIENTLY HOT MAY IGNITE EVEN LIQUID PRODUCT IN THE ABSENCE OF SPARKS OR FLAME. EXTINGUISH PILOT LIGHTS, CIGARETTES AND TURN OFF OTHER SOURCES OF IGNITION PRIOR TO USE AND UNTIL ALL VAPORS ARE GONE. VAPORS MAY ACCUMULATE AND TRAVEL TO IGNITION SOURCES DISTANT FROM THE HANDLING SITE; FLASHFIRE CAN RESULT. KEEP CONTAINERS CLOSED WHEN NOT IN USE. USE WITH ADEQUATE VENTILATION.

CONTAINERS, EVEN THOSE THAT HAVE BEEN EMPTIED, CAN CONTAIN EXPLOSIVE VAPORS. DO NOT CUT, DRILL, GRIND, WELD OR PERFORM SIMILAR OPERATIONS ON OR NEAR CONTAINERS. STATIC ELECTRICITY MAY ACCUMULATE AND CREATE A FIRE HAZARD. GROUND FIXED EQUIPMENT. BOND AND GROUND TRANSFER CONTAINERS AND EQUIPMENT.

DO NOT STORE OR HANDLE IN ALUMINUM EQUIPMENT AT TEMPERATURES OVER 120 DEG. F.

SECTION XIII

TRANSPORTATION REQUIREMENTS

DEPARTMENT OF TRANSPORTATION CLASSIFICATION: FLAMMABLE LIQUID  
D.O.T. PROPER SHIPPING NAME: BUTYL ALCOHOL

OTHER REQUIREMENTS:

NA1120. GUIDE SHEET 26.

SECTION XIV

OTHER REGULATORY CONTROLS

THIS PRODUCT IS LISTED ON THE EPA/TSCA INVENTORY OF CHEMICAL SUBSTANCES.

THE INFORMATION CONTAINED HEREIN IS BASED ON THE DATA AVAILABLE TO US AND IS BELIEVED TO BE CORRECT. HOWEVER, SHELL MAKES NO WARRANTY, EXPRESSED OR IMPLIED REGARDING THE ACCURACY OF THESE DATA OR THE RESULTS TO BE OBTAINED FROM THE USE THEREOF. SHELL ASSUMES NO RESPONSIBILITY FOR INJURY FROM THE USE OF THE PRODUCT DESCRIBED HEREIN.

DATE PREPARED: OCTOBER 31, 1985

JOHN P. SEPESE

BE SAFE

READ OUR PRODUCT  
SAFETY INFORMATION ...AND PASS IT ON  
(PRODUCT LIABILITY LAW  
REQUIRES IT)

SHELL OIL COMPANY  
PRODUCT SAFETY AND COMPLIANCE  
P. O. BOX 4320  
HOUSTON, TX 77210